



Specification Sheet for **Acecube** Offshore Fuel Tanks

APPROVALS & CERTIFICATIONS

- ✓ UL 142, ULC S601
- ✓ PPG2 & PPG26 Compliant
- ✓ Vibration tested
- ✓ Designed & built in UAE
- ✓ DNV Certified



DESIGN FEATURES

- Certified and approved bunded fuel tanks, compliant with Pollution Prevention Guidelines.
- Lifting when full Certified.(450L-3000L)
- Bidirectional fork lift pockets, internal baffles & galvanised lifting eyes to allow easy and safe handling.
- Designed to stack inside shipping containers & across truck beds providing economical transportation.
- Unique hex corners for extra strength.
- Hose openings in front of tank, allow to be use when locked.
- Provisions for dispensing unit.
- Connections with provisions for additional feed & returns for multiple equipment use.
- Bunded outer tank capacity 110% of volume & removable inner tank for maintenance.
- Two lifting plates on primary/inner tank, one at each end, which are removable for maintenance/access.
- Space efficient design: easily stacked 2 high & 3 high when empty. (refer chart for detail)
- Three feed & three returns for multiple equipment use.
- Primary and secondary hatch plates for multiple use and versatility. The primary hatch plate acts as a man way.
- The primary hatch plate comes complete with secure lockable design.

SEPECIAL FEATURES

- ✓ DNV certified tank.
- ✓ Built for offshore conditions.
- ✓ Customized to customer requirements
- ✓ 110% banded tank
- ✓ Galvanized base frame & side frame
- ✓ Galvanized hatch plates
- ✓ Galvanized stacking corners

ACECUBE OFFSHORE MODEL	CAPACITY	DIMENSIONS (MM)	WEIGHT (KG)		APPROVALS				STACKABILITY		LIFTING	
			EMPTY	FULL	UL 142	ULC 1206	UN/ADR 31AY	BS 799	EMPTY	FULL	EMPTY	FULL
ACO	LTR	L X B X H										
ACO - 950L	950	1552x1017x1074	640	1495	✓	✓	✓	✓	3	2	✓	✓
ACO - 2000L	2000	2552x1096x1074	940	2740	✓	✓	✓	✓	3	2	✓	✓
ACO - 3000L	3000	2552x1602x1074	1180	3880	✓	✓	✓	✓	3	2	✓	✓

PRIMARY HATCH PLATE



CORNER STACKING/
LIFTING BRACKET



SAFETY DECALS



PUMP MOUNTING BRACKET

